


Mini 60A

High Precision
Cleaver


One-click Operation Cleaver



One-Click



Precise



Long life-span



Easy rotating



Counter

01 Performance



02 Multi-Functional Holder

Removable / Universal



03 One-Click Operation




04 Easy Blade Rotating



05 Long Life-Span 60,000



06 Digital Counter



07 Auto Chip Collector

Specifications

Type	Single & ribbon fiber cleaver
Operation method	One click cleaving
Weight / Dimension	265g / 105*108*56mm(with Auto chip collector), 105*90*56mm(with trash bin)
Cladding Diameter	80~125um
Cleaving Length	Single Fiber:10~20mm / Ribbon fiber: 10mm
Applicable Fiber	Single Fiber: 250um, 900um, 3.0mm fiber cable and indoor cable / Ribbon fiber: 2 to 12 ribbon fiber cable
Average Cleaving Angle	Single Fiber: 0.3°~0.9° (Ave.0.5°) / Ribbon Fiber: 0.3°~1.2° (Ave.0.5°)
Typical Blade Life Span	60,000 times
Holder	Single: Screw lock type_Universal(0.25~3.0mm) / Ribbon: Magnetic detachable type_Individual (2,4,6,8,12CH)



(Kwang Yi Building) 80, Dongseo-daero 179beon-gil,
Yuseong-gu, Daejeon 34159, Korea
Tel +82-42-716-7221 / Fax +82-42-716-7223 / Email sales@fiberfox.co.kr

www.FiberFox.co.kr